LLC «TechnoNICOL — Construction Systems» www.tn-europe.com info@tn-europe.com



DECLARATION OF PERFORMANCE Nr. XPS/008/CE/2016

1. Unique identification code of the product-type:

TECHNONICOL CARBON ECO d= 20, 30, 40 mm

"F" (facade) - in the presence of surface topography on both sides of the board;
"D" (drainage) - in the presence of drainage channels on the surface of one side board;
Symbol plates supplemented with the words "SLOPE" with the designation of an appropriate slope in%

2. Intended use/es:

Heat-insulating cellular polystyrene extruded boards TECHNONICOL CARBON ECO are used for industrial, civil and transport engineering as heat-insulation of building constructions in the temperature range of -70 to +75°C.

3. Manufacturer:

«Zavod Tehnoplex » Ltd. Vostochny Promuzel 21 Ryazan, Russia, 390047 Tel.: +7 (4912) 911-355 Fax.: +7 (4912) 911-356

- 4. Authorised representative:
- 5. System/s of AVCP:

System 3

6a. Harmonised standard:

Test report No. 75 35 00962/2014

Notified body/ies:

№ 1023. Institute of tests and certification, PLC Institut pro testování a certifikaci, a.s. třída Tomáše Bati 299, Louky 763 02 Zlín Česká republika/Czech Republic tel/phone: + 420 577601541

1 2

7. Declared performance:

E-XPS- EN 13164-T1-CS(10)200-DS(TH)-WL(T)0.7-WD(V)3

| | Essential characteristics | Test method | Unit of measurement | Properties | Harmonized technical specification |
|----|---------------------------------------------------|-------------|---------------------|-----------------------------------------------------------------------|------------------------------------|
| 1 | Thermal conductivity, λD | EN 12667 | W/m² K | 0.034 | EN 13164 |
| 2 | Thermal resistance, RD | EN 12667 | m²*K/W | 20 mm - 0.588 30 mm - 0.882 40 mm - 1.176 | |
| 3 | Thickness, class T1 | EN 823 | mm | 20, 30, 40 | |
| 4 | Width | EN 822 | mm | 580, 600 | |
| 5 | Length | EN 822 | mm | 1180, 1200, 2380, 2400, 4000 | |
| 6 | Reaction to fire, Euroclass | EN 13501-1 | | Class E | |
| 7 | Cornpressive stress under 10% deformation, CS(10) | EN 826 | kPa | ≥ 200 | |
| 8 | Long term water absorption by immersion, WL(T) | EN 12087 | % | ≤ 0.7 | |
| 9 | Long term water absorption by diffusion, WD(V) | EN12088 | % | ≤ 3.0 | |
| 10 | Dimensional stability, DS(TH) | EN 1604 | % | Relative change of length, width and thickness not exceeding 5% | |

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S. Benz General Director, «Zavod Tehnoplex» Ltd

Завод

ТЕХНОПЛЕКС

Ryazan, 25.07.2016